

## Instructions

Ball lock complete assembly with mini CO2 kit.

Take your keg to the party – no need to carry bulky CO2 apparatus.



## Warnings:

- Read instructions before use.
- Keep CO2 cartridge away from heat or direct sunlight.
- Let the cartridge empty completely before disconnecting from regulator.
- Cartridges are not refillable.

## Included in the Kit:

- Mini Regulator attached to Ball lock gas disconnect.
- 2 CO2 cartridges , 74 gm ea.
- Ball lock liquid disconnect with picnic faucet.

## Instructions:

- Attach the black plastic disconnect to the liquid side of the keg.
- Ensure that the knob on top of mini regulator is turned all the way clockwise so that it is shut off.
- Screw in the CO2 cartridge to bottom of mini regulator making sure that the cartridge gets punctured and is screwed in all the way.
- Attach grey ball lock disconnect and mini regulator assembly to the gas side of your keg.
- Turn the knob on mini regulator counter-clockwise very slowly to let the gas flow. Go slow and in small increments until the desired pressure is reached.
- Once the right pressure is achieved there should be no need to make any further adjustments during use.
- Pour beer from the picnic faucet.
- Shutoff gas from regulator when done to use next time. Do not unscrew partially full cartridge.
- Once the cartridge is empty it can be unscrewed and discarded (recycled). Shutoff regulator by turning clockwise before screwing in new cartridge.

